

- 1.- Identification Code Product Type: POLYLIT-P28-LTR
- 2.- Type (allows identification of the product): POLYLIT / Nº layers Gel coat / Profile Code / Day-Month-Year / Hour
Cream thread (indicative thickness= 0,7 mm)
- 3.- Intended use of the product: Light transmitting profiled plastic sheets, which are used as a single layer or when assembled to form multiple layer construction, for:
- Discontinuously laid floor covering for buildings
- Internal and external wall and ceiling finishes
- 4.- Manufacturer: STABILIT EUROPA, S.L.U., Ctra de Ripollet B-141, Km 3,9 (Polígono Santiga), 08130 Santa Perpétua de la Mogoda, Barcelona (Spain)
- 5.- Authorised representative: Not Applicable
- 6.- System of assessment and verification of constancy of performance of the product: System 3
- 7.- Declaration of performance of the product by harmonised standard: EN 1013:2013
NB-0370, Applus. Notified Testing Laboratory under System 3
Determination of the Product-Type on basis of type testing of External Fire Performance.
- 8.- Declaration of performance of the product by European technical assessment: Not Applicable
- 9.- Declared performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Small Hard body Impact Resistance	Pass	EN 1013:2013
Large Soft body Impact Resistance (assembly)	Fail (XP P 38-505:98)	
External Fire Performance	B roof (t1)	
Reaction to Fire	F (NPD)	
Water Vapour Permeability	1,5 x 10 ⁻⁵ mg/(m·h·Pa)	
Water / Air Permeability	Pass	
Dimensional Tolerances:	Pass	
Durability (after ageing), as:		
- Variation of Yellow Index	NPD	
- Variation of Light Transmittance	NPD	
Release of dangerous substances	NPD	

NPD: No performance determined (in test process)

- 10.- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:



Joan Vila, General Manager

Santa Perpétua de la Mogoda, 26/09/2014

REACH Article 33, Communication of information on substances in articles: According to Article 33 of Regulation (CE) Nº 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) inform that our products (articles) do not contain a SVHC (Substances of Very High Concern) included in the list of candidate substances in a concentration above than 0.1% (w/w).



NB-0370

STABILIT EUROPA, S.L.U.
Ctra Ripollet B-141, Km 3.9,
08130 Santa Perpétua de la Mogoda (Barcelona) Spain

14

CPR-P28-LTR-01-1409

EN 1013:2013

Light transmitting profiled plastic sheets, which are used as a single layer or when assembled to form multiple layer construction, for:

- Discontinuously laid floor covering for buildings
- Internal and external wall and ceiling finishes

POLYLIT-P28-LTR

GRP sheets

Small Hard body Impact Resistance	Pass
Large Soft body Impact Resistance (assembly)	Fail (XP P 38-505:98)
External Fire Performance	B roof (t1)
Reaction to Fire	F (NPD)
Water Vapour Permeability	$1,5 \times 10^{-5} \text{ mg/(m}\cdot\text{h}\cdot\text{Pa)}$
Water / Air Permeability	Pass
Dimensional Tolerances:	Pass
Durability (after ageing), as:	
- Variation of Yellow Index	NPD
- Variation of Light Transmittance	NPD
Release of dangerous substances	NPD
	IM-248 (270814-00)